

Modern HydroTap Deck Mount BC Classic Faucet

Style Number: 825190

Collection: HydroTap

Origin: Australia

Description: HydroTap Deck Mount Boiling & Chilled Filtered Faucet Bright Chrome 240V



GENERAL FEATURES & SPECIFICATIONS

- Deck Mounted Classic Filtered Faucet w/ Boiling & Chilled
- For Large Commercial Applications
- Boiling Water Safety Lock, Cool Touch Tap
- Smart Energy Saving Mode
- Hole Size: 1-3/8"
- Flow Rate: Max 1.8gpm
- Water Pressure: Min 30psi-Max 75psi, Min Flow 1gpm
- Water connection: 1/2" BSP Isolation Valve Required within 3' of installation
- Integral Water Valves: Fitted with a Dual Check Valve and 50psi Pressure Limiting Valve
- Water Supply Requirements: Potable Drinking Water
- TDS: Min 50ppm – max 120ppm
- Integral Water Filter: 0.2 Micron, 1.5 Size – Replace every 1800 gallons or 6 months
- Power Rating: 220-240V, 50Hz, 2.2kW
- Power Supply: 220-240V, 50/60Hz 15amp power supply with NEMA 6-15 Outlet
- Dimension: 15.5" x 18.3" x 13.1"
- Min Air Gap: Clearances are required 2" Left Side, 2" Right Side, 8" Above
- Approvals: WQA – NSF/ANSI 372, 42, 53, cUL, CEC, ADA
- Available Finishes: Bright Chrome, Brushed Chrome, Matte Black

